

Staticmaster® Ionizing Air Nozzle



TECHNOLOGY
& LAB



INDUSTRIAL

MODEL NUMBER 6108

CORONA

The Staticmaster Ionizing Air Nozzle provides efficient, point-of-use ionization for fast discharge times and precise charge neutralization for the most critical manufacturing environments.

The Model 6108 is ideal for use where a compact, lightweight and highly reliable source of ions is needed for static control.

APPLICATIONS

- Electronic assembly
- Medical device assembly
- Printing
- Packaging

FEATURES

- Auto ion balance
- Normal and abnormal running indicator and lights
- Small and Light weight

BENEFITS

- Automatic ion balance
- Fits into small spaces
- Removes static quickly

EVERY SITUATION IS UNIQUE. SO IS EVERY SOLUTION.®




Staticmaster® Ionizing Air Nozzle

MODEL NUMBER 6108

CORONA

SCHEMATICS



SPECIFICATIONS

Balance: ±10 V

Dimensions: 4.12in W x 2.23in H x 0.87 in L (104.5mm x 56.5 mm x 22 mm)

Gas Input: 10-70 psi, Clean Dry Air (CDA) or Nitrogen

Line Connection: 6 mm

Operating Humidity: 30-70%

Operating Voltage: 24 V DC

Technology: Corona

Weight: 0.2 lbs. (0.09 kg)

DECAY RATE: 0.5 seconds positive, 0.6 seconds negative (±1000 to 100V), ANSI/ESD Association STM 3.1 @ 1 foot, center

MAINTENANCE

It is necessary to clean and balance ionizer regularly. Clean emitter points as needed.

NOTICE: NRD expressly warrants that for a period of one (1) year from the time of purchase, the ionizer will be free of defects in material (parts) and workmanship (labor).

NRD, LLC USA

800-525-8076
716-773-7634
Sales@NRDLLC.com
2937 Alt Boulevard
PO Box 310
Grand Island, NY
14072-0310 USA

NRD Asia Pte. Ltd.

+65 6679 1707
Sales@NRDAsia.com
114 Lavender Street
#08-90 CT Hub 2
Singapore 338729

To learn more, contact an NRD representative for a consultation at **1-800-525-8076** or visit **nrdstaticcontrol.com**.

